
TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES for HIGHWAY CONSTRUCTION, CONTRACT MAINTENANCE and UTILITY OPERATIONS



SYMBOLS

WORK AREA

- ▶ SIGN ON PORTABLE OR PERMANENT SUPPORT
- → TYPE II BARRICADE W/TYPE A FLASHING LIGHT
- O DRUM WITH STEADY BURNING LIGHT

ADVANCE WARNING SIGN SPACING TABLE		
POSTED SPEED LIMIT	DISTANCE BETWEEN SIGNS "D"	
40 MPH or less	200 FEET	
45-50 MPH	350 FEET	
55 MPH	500 FEET	

GENERAL NOTE:

This Standard is used where at any time, day or night, any vehicle, equipment, workers or their activities encroach on the pavement or where construction requires lane closures.

DESIGN NOTES:

- For a side road with a speed limit of 40 mph or less, the closed portion of the main route shall be
 protected by blocking with Type II barricades or drums, 1/3 of the cross section of the closed
 portion of the roadway.
- For a side road with a speed limit of 45 mph or greater, the closed portion of the main route shall be protected by blocking with Type II barricades or drums, 1/2 of the cross section of the closed portion of the roadway.
- 3. All W20-1 "ROAD WORK AHEAD" signs shall be 48"x48" with fluorescent orange reflective sheeting with an amber Type A flashing light mounted on the sign.
- When the side road lies between the beginning of the mainline signing and the work zone, a M6-1 Single Headed Arrow shall be used in lieu of the M6-4 Double Headed Arrow.
- 5. For a lane closure on a side road, use the applicable portions of the appropriate Highway Standard or Traffic Control Detail. The spacing of the signs and barricades or drums shall be adjusted for field conditions as directed by the engineer. The directional arrow shall be covered or removed when no longer consistent with the side road closure.
- 6. Advance warning signs shall be omitted on driveways unless otherwise noted.
- The traffic control and protection for side roads and intersections shall be included in the contract lump sum price for "TRAFFIC CONTROL AND PROTECTION, SPECIAL."

MODIFIED IDOT DISTRICT ONE SIDE ROAD DETAIL

REVISIONS	DATE	≥ LakeCounty	APPROVED BY: ANTHONY KHAWAJA	
Title Block Revision	8/1/09	LakeCounty Division of Transportation	DATE: APRIL I, 2007	_
Reformat LCDOT Standard	7/15/10			Ċ
Use of Drums in lieu Type III Barricade	4/22/14	TRAFFIC CONTR	OL and PROTECTION	2
		for SIDEROAD	S, INTERSECTIONS RIVEWAYS	4

NOT TO SCALE